



瑞雕高速龙门精雕机
Ruidiao High-speed gantry carving machine

AB系列 AB-series models



- X、Y、Z轴均采用重型滚珠式导轨，减少机床加工过程中的摆动，具有更高精度的加工能力。
- X\Y\Z axes use heavy-duty ball guide rails to reduce swinging during machine processing and have higher precision machining capabilities.
- 整体床身全部采用大理石花岗岩制作而成，床身受温度和应力的影响而变形的程度会降低。
- The entire machine bed is constructed using marble granite, significantly reducing the degree of deformation caused by temperature and stress variations.
- 机床采用后背式电柜，这种紧凑型设计使得机床占用的空间极致的减少。
- The machine tool employs a rear-mounted electrical cabinet, a compact design that maximizes space efficiency and minimizes the occupied footprint.
- 采用NK500面板，常用功能一键直达，节约操作时间，面板可旋转，节省车间空间。
- Using the NK500 CNC system, commonly used functions can be accessed with just one click, saving operation time. The panel can rotate, saving workshop space.
- 台面以上采用不锈钢钣金，使得机床具备了使用自来水作为切削液的能力，降低使用成本。
- The use of stainless steel sheet metal above the tabletop enables the machine tool to utilize tap water as cutting fluid, thereby reducing operational costs.



安徽瑞苏科技有限公司
ANHUI RUISU TECHNOLOGY CO.,LTD.

设备图片仅供参考，配置和参数如有更改，恕不另行通知。本手册的最终解释权归安徽瑞苏科技有限公司所有。
The pictures of the equipment are for your reference only. The configurations and parameters are subject to change without notice.
The final interpretation of this brochure is owned by Anhui Ruisu Technology Co.,Ltd.

AB系列 AB-series models

标准配置Standard

- NK500数控系统
- NK500Control System
- 自动对刀仪
- Cutter Aligner
- 大理石床身
- Marble Machine Base
- 自动丝杆导轨润滑系统
- Lubrication Systems
- 主轴冷冻机
- Spindle Chiller
- Bt30刀库
- BT30 Tool Changer

可选配置Optional

- 真空吸附台面
- Vacuum adsorption table
- 水环式真空泵
- Water Ring Vacuum Pump

技术参数Technical Specification

机型Model	AB1080	AB1290
X/Y/Z运动定位精度(MM) Position Accuracy (X/Y/Z)(in.)	0.010/0.010/0.008 0.0004"/0.0004"/0.0003"	
X/Y/Z重复定位精度(MM) Repeatability (X/Y/Z)(in.)	0.005/0.005/0.005 0.0002"/0.0002"/0.0003"	
X/Y/Z工作行程(MM)(in.) Travel (X/Y/Z)	1,000X800X220 39.3"X31.5"X8.7"	1,200X900X220 47.2"X35.4"X8.7"
工作台尺寸(MM) Worktable Size(in.)	1,000X800 39.3"X31.5"	1,200X900 47.2"X35.4"
最大工作负重(Kg) Max. Load(lb.)	500 1,100	600 1,300
主轴最高转速(rpm) Max. Spindle Speed		3,000~24,000rpm(Φ120)
刀库容量 Tool Magazine Capacity		12/16
刀柄规格 Tool Holder Type		BT30
快速系统速度(M/min) Max. Rapid Rate (X/Y/Z)(in/min)		18 708
最高切削给进速(M/min) Max. Feed Rate (X/Y/Z)(in/min)		12 472
驱动系统 Drive System		维宏总成 Weihong AC servo
工作电压(V) Voltage		三相380V/50Hz 3-Phase, 380V/50Hz
气源压力(MPa) Air Pressure		0.6
机床重量(Kg) Machine Weight(lb.)	3,400 7,500	4,500 10,000
电柜尺寸(MM) Controlling cabinet size (in.)		-
机床尺寸(MM) Machine Dimension(in.)	2,250X2,550X2,400 88.6"X100.4"X94.5"	2,450X2,750X2,400 96.5"X108.2"X94.4"